

QUBE POWER MAX HYBRID PORTABLE LIGHT TOWER

QPMH-2H-AU



Features

Battery Bank AGM 4 x 150Ah @ 24VDC 300Ah with battery monitor
3hrs Runtime @ full brightness of 1200W
24V 60A Battery charger 2.5hrs from discharge to 80% charge and 5.5hrs to 100%
Battery Bank can also be charged from mains power
Selector switch - Hybrid/Genset, Grid power or off
Mitsubishi L2E Engine, 2 cylinder, 4 stroke, water cooled, 4.4kw at 1500rpm
NSM (Italy) Brushless alternator, 3.5kW @ 1500rpm (230VAC single phase @50Hz)
4 x high lumen output 300W LED with special asymmetric lenses. 40/60 degrees. LED drivers are Meanwell and CE certified
156,000 lumens / 4800m2
Deepsea 4520 Genset Controller
Electric or manual light bar tilt
350° Mast rotation
Each LED Light can also be individually angled before raising mast
7 metres 12v Hydraulic or Manual winch mast
Heavy Duty 890CCA Battery
110% Bunding
60 liters (DIESEL)
58dB at 7 metres
ALKO torsion suspension or optional Leaf springs
ALKO Drawbar with 50mm ball hitch and inertial braking
4 x Extendable heavy duty stabilizer outriggers
Powder coated with PP powder that is UV and corrosion resistant with many colour options
LED Tail lights and license plate light, 7pin flat plug
13" Sunraysia Rims with ADR approved light truck tyres
Centre point lifting
Forklift pockets on all 4 sides
Trailer has full ADR approval
Olikara's uniquely engineered canopy with raise and side opening doors for complete access
Compact and Lightweight
Dimensions (Travel) LxWxH(metres) - 2.4 x 1.18 x 2.3
Dimensions (Operational) LxWxH(metres) - 2.4 x 2.74 x 7
Weight - 1130kg

****Light Tower can be customised to suit your specifications****

24 months/2000hrs on Mitsubishi engines, 12 months on NSM alternators and 12 months on structure.

For more information please call Russ on 0430 606 692

Email: sales@lightequip.com.au or visit www.lightequip.com.au Ph 1300 548 362

Lighting Equipment Pty Ltd

ACN680 480 915